


# Stepsolve Anti-Slip

TACTILE INDICATORS & OTHER PRODUCTS




*Stepsolve's architectural Tactile Ground Surface Indicators are available in austenitic 316 stainless steel, and UV stable polymer. All Stepsolve tactiles meet the required safety standards for the Building Code of Australia (BCA), Australian and New Zealand Standards (AS/NZS:1428) and The Disability Discrimination Act (DDA)*



## TT-DL

Individual 316 Stainless Steel tactile indicator with Drill & Lock. Top of dome 25mm. Bottom of dome 35mm. Spigot diameter 8.5mm. Length 22mm. R13 Rated.




## TWT-PS

TacWay Tile peel & stick adhesive backing. 300mm x 300mm UV Stable Polymeric. Colours: Black, Yellow, Grey, Ivory, Terracotta. R11 Rated.




## TT-FS

Individual 316 Stainless Steel flat tactile indicator. Top of Dome 25mm. Bottom of dome 35mm. No stem. R13 Rated.



## TT-SS PLATE

316 Stainless Steel tactile indicator plate. 300mm x 600mm x 2mm base plate. Includes 72 tactile indicator buttons and 6 tapered screw holes and screws. Available with Polymeric or Carborundum infill. R13 Rated.



## TT-SS

Individual 316 Stainless Steel tactile indicator with stem. Top of Dome 25mm. Bottom of dome 35mm. 13mm stem. R13 Rated.



## TT-TWP

TacWay Pad 900mm x 600mm UV Stable Polymeric Tactile Pads. Colours Black, Yellow, Grey, Ivory, Terracotta. R11 Rated



## TT-SH

Individual 316 Stainless Steel tactile indicator with screw & hole. Top of Dome 25mm. Bottom of dome 35mm. R13 Rated.



## TT-TS

TacStuds. Individual UV Resistant Polymer tactile indicator. Top of dome 25mm, Bottom of dome 35mm. Spigot diameter 8mm. Stem length 22mm. R11 Rated.



## TT-SC

Individual 316 Stainless Steel tactile indicator with stem & carborundum inset. Top of Dome 25mm. Bottom of dome 35mm. 8mm stem. R13 Rated.



## TT-SD

Individual 316 Stainless Steel directional tactile indicator with spigots. 35mm x 295mm x 5mm height. 3 spigots 12mm length x 6mm diameter.



## TT-DLC

Individual 316 Stainless Steel Drill & Lock tactile indicator with carborundum inset. Top of dome 25mm. Bottom of dome 35mm. Spigot diameter 8.5mm. Length 22mm. R13 Rated.



## CDB-1

Tactile diamond core drill bits. High quality metal drill bit for use when core drilling into tiles & all hard surfaces for tactile installation. 100mm length. Available in 6mm, 7mm & 8mm diameters.



## TT-DLP

Individual 316 Stainless Steel tactile indicator with Drill & Lock technology and polymer inset. Top of dome 25mm. Bottom of dome 35mm. Spigot 8.5mm. Length 22mm. R11 Rated.



## ADHESIVES

Mapei TacWay Pad Adhesive in 2kg and 5kg tubs. AkepoX individual tactile adhesive tubes.

*The company with every floor and step safety solution.*

**Stepsolve Australia:** Unit 3/29 Adam Street Hindmarsh SA 5007 Ph: 08 8340 9964

Fax: 08 8340 9968 Mobile: 0466 309 222 Email: [info@stepsolve.com.au](mailto:info@stepsolve.com.au) Web: [www.stepsolve.com.au](http://www.stepsolve.com.au)